



FIG:F1361FFCL(F1361FFCS)

NOTE:1. THE TORQUE BETWEEN
BODY AND END PLUG
3/8" MIN 280 IN-LBS
1/2" MIN 375 IN-LBS

				11	THREAD COVER	2	PLASTIC	
				10	END PLUG	1	ASTM B124-C37700 JIS H3250-C3771B	同A5-10
				9	BALL DISC	1	ASTM B16-C36000 JIS H3250-C3604B	同A4-09
				8	BALL DISC TEFLON	2	TEFLON PTFE	同A4-08
				7	BODY	1	ASTM B124-C37700 JIS H3250-C3771B	
				6	NAME PLATE	1	ASTM B209-1100 JIS H4000-A1100P	同A4-06
				5	GLAND PACKING	1	TEFLON PTFE	同A4-05
				4	STEM GLAND SCREW	1	ASTM B16-C36000 JIS H3250-C3604B	同A4-04
				3	STEM	1	ASTM B16-C36000 JIS H3250-C3604B	同A4-03
1/2	67	10	3/4-16UNF	2	HANDLE	1	ASTM B86-AC41 JIS H5301-ZDC1	同A4-02
3/8	64	7	5/8-18UNF	1	SCREW	1	AISI-1010 JIS S10C	同A4-01
SIZE	L	d1	THD	NO	PARTS NAME	PCS	MATERIAL	SPEC

△									
△					件號	零件名稱	件數	材質	規範
△					比例	單位 mm 第三角法	名稱	GAS BALL VALVE (FLARE X FLARE)	
順序	修訂事項			日期	修訂者				
設計	金庸	會簽		審核	富山精機廠股份有限公司			圖號	A6-00
設計	98年05月20日								△3