



FIG: F1361GTL(F1361GTS)

NOTE: 1. THE TORQUE BETWEEN BODY AND END PLUG
 1/2" MIN 375 IN-LBS
 3/4" MIN 560 IN-LBS

12	PLUG	1	ASTM B16-C36000 JIS H3250-C3604B							
10	END PLUG	1	ASTM B124-C37700 JIS H3250-C3771B	同A4-10						
9	BALL DISC	1	ASTM B16-C36000 JIS H3250-C3604B	同A4-09						
8	BALL DISC TEFLON	2	TEFLON PTFE	同A4-08						
7	BODY	1	ASTM B124-C37700 JIS H3250-C3771B							
6	NAME PLATE	1	ASTM B209-1100 JIS H4000-A1100P	同A4-06						
5	GLAND PACKING	1	TEFLON PTFE	同A4-05						
4	STEM GLAND SCREW	1	ASTM B16-C36000 JIS H3250-C3604B	同A4-04						
3	STEM	1	ASTM B16-C36000 JIS H3250-C3604B	同A4-03						
3/4	65	35	15	25	41	2	HANDLE	1	ASTM B86-AC41 JIS H5301-ZDC1	同A4-02
1/2	57	31	10	23	37	1	SCREW	1	AISI-1010 JIS S10C	同A4-01
SIZE	L	H	d	E	H1	NO	PARTS NAME	PCS	MATERIAL	SPEC

△											
△							件號	零件名稱	件數	材質	規範
△	把手字體變更				90 06/06	綜 日期	比例	單位 mm	第三角法	名稱	GAS BALL VALVE(WITH TAP)
順序	修訂事項										
設計	金庸	會 簽					富山精機廠股份有限公司			圖號	A8-00
計	98年05月20日										△ 4