



FIG:F1361FFTL(F1361FFTS)

NOTE:1. THE TORQUE BETWEEN  
BODY AND END PLUG  
3/8" MIN 280 IN-LBS  
1/2" MIN 375 IN-LBS

12	PLUG	1	ASTM B16-C36000 JIS H3250-C3604B	同A8-12						
11	THREAD COVER	2	PLASTIC	同A5-11						
10	END PLUG	1	ASTM B124-C37700 JIS H3250-C3771B	同A5-10						
9	BALL DISC	1	ASTM B16-C36000 JIS H3250-C3604B	同A4-09						
8	BALL DISC TEFLON	2	TEFLON PTFE	同A4-08						
7	BODY	1	ASTM B124-C37700 JIS H3250-C3771B							
6	NAME PLATE	1	ASTM B209-1100 JIS H4000-A1100P	同A4-06						
5	GLAND PACKING	1	TEFLON PTFE	同A4-05						
4	STEM GLAND SCREW	1	ASTM B16-C36000 JIS H3250-C3604B	同A4-04						
3	STEM	1	ASTM B16-C36000 JIS H3250-C3604B	同A4-03						
2	HANDLE	1	ASTM B86-AC41 JIS H5301-ZDC1	同A4-02						
1	SCREW	1	ASI-1010 JIS S10C	同A4-01						
1/2	74	36.5	37.5	10	3/4-16UNF	2				
3/8	71	34.5	36.5	7	5/8-18UNF	1				
SIZE	L	E	F	d1	THD	NO	PARTS NAME	PCS	MATERIAL	SPEC

△										
△						件號	零件名稱	件數	材質	規範
△	把手字體變更				90 06/06	綜 日期	比例 /	單位 mm	第三角法	名稱 GAS BALL VALVE (FLARE X FLARE) WITH TAP
順序	修訂事項									
設計	金甯	會 簽					富山精機廠股份有限公司	圖 號	AA-00	△ 3
設計	98年05月20日									